

**Type PMA-DS-05-Q1R-SP**  
**Panel Mount Fuse Holder**  
**1/4" x 1 1/4" (6.3 x 32mm) Fuses**  
**Driver / Screw – Spashproof Cap**



www.optifuse.com (619) 593-5050


**Electrical Rating:** 15A, 250V AC  
**Fuse Style:** 1/4" x 1 1/4" (6.3 x 32mm)

**Material:**  
**Frame and Cap:** PBT (UL flame: 94V-0)  
**Terminals:** Tin-plated brass  
**Cap:** Slotted Driver type, Screw type – **Spashproof Cap IP55**  
**Mounting:** by nut

**Terminal:** Solder/Quick-Connect 4.8mm / 0.187"  
**Panel Thickness:** 0.5 ~ 4.5mm  
**Agency Standards and Listings:**



**Product Dimensions: Inches [mm]**



<p><b>Warning:</b></p>	<ul style="list-style-type: none"> <li>-Operation beyond the specified maximum ratings or improper use may result in damage and possible electrical arcing and/or flame.</li> <li>-Fuse Holders are not intended for circuit disconnect. All power should be disconnected before removing fuse.</li> <li>-Avoid contact of Fuse Holder with chemical solvent. Prolonged contact may damage the device performance.</li> </ul>
------------------------	---